



## **STYLE**

**Applied Color**  
**YB292226**

**Composition**  
**vinyl coating on woven cotton backing**

**Width**  
**130 cm , 51 inches**

**Length**  
**30 meters per roll**

**Weight**  
**450 gr/m<sup>2</sup> , 20 oz/yd**

**Performance**  
**Flame retardancy:**  
**ASTM E-84, class A**  
**EN 13501, class B-s1, d0**  
**BS 476-7, class 2**  
**GB 8624-2012, class B1**

**Composition safety:**  
**CDPH 01350, low VOC compliant**  
**GB 18585-2001, pass**  
**JIS Z 2801:2010 applicable**

**Physical performance:**  
**ASTM D4060-25, abrasion resistance**  
**ASTM D2261-13, wet tear strength**  
**ASTM D5034-21, grab tensile strength**


**Installation**  
**Suggested to apply primer sealer and SL 001 glue combination to install. Overlap of 1" of two strips and cut in middle is suggested for butt treatment. Installation advice supplied with every roll.**

**Variation**  
**There can be a variation between sample material and finished product. Stock cuttings are available for color approval.**



## **STYLE**

**YB292223**



**YB292224**



**YB292225**



**YB292226**



**YB292228**



**YB292229**



**YB292230**



**YB292232**

